Secure Enterprise Communication: A Deterministic Approach to WebRTC Signaling and IDOR Mitigation

Muhammad Furqan Hakim[1]
[1]Information System, Universitas Graha Karya Muara Bulian, Jl. Gajah Mada, Teratai, Muara Bulian, Jambi, 36612, Indonesia
[1]mfurqanhakim139@unama.ac.id

Abstract

The exponential growth of bloated web development frameworks and the pervasive reliance on centralized, third party video conferencing infrastructures present critical challenges in computational overhead, structural friction, and digital sovereignty. This study introduces a novel zero dependency micro architecture, a custom built, highly optimized model view controller paradigm integrated with an embedded web real time communication engine, designed specifically for resource constrained environments. To address escalating cybersecurity threats, the architecture formalizes an entropy based alphanumeric indexing protocol, effectively neutralizing insecure direct object reference vulnerabilities without the computational cost of complex intermediate software. Employing a rigorous socio technical methodology, this research bridges quantitative computational analysis with qualitative sociological frameworks. Performance evaluations demonstrate that the zero dependency architecture significantly outperforms contemporary mainstream frameworks in memory utilization, request latency, and quality of service stability under high concurrency signaling. Sociologically, drawing upon functionalism and phenomenology, the study elucidates how this decentralized, customized communication subsystem restores data sovereignty, centralizes managerial control, and reshapes the lived experiences of the users regarding privacy and professional trust. The findings contribute a new paradigm to software engineering and digital sociology, proving that minimalist custom architectures offer a superior, sustainable alternative for secure enterprise communication, effectively challenging the necessity of heavily abstracted technological stacks.

Keyword: *Zero Dependency Architecture, Web Real Time Communication, Digital Sovereignty, Security Vulnerability Mitigation, Green Computing, Socio Technical Systems*

.

I. INTRODUCTION

The rapid acceleration of digital transformation within the Industry 5.0 paradigm has fundamentally reshaped organizational identities and the dynamics of digital platforms [1]. As organizations transition toward advanced digital technology adoption [2], there is an increasing demand for innovation ecosystems that can sustain regenerative growth. However, this shift is often accompanied by a reliance on bloated software frameworks and centralized third-party infrastructures that exacerbate computational overhead and energy consumption. Achieving verified decarbonization in the digital sector requires the establishment of energy baselines [3] and sustainable structural engineering solutions [4]. Consequently, there is a critical need for a "green" software paradigm—specifically a zero-dependency micro-architecture—that aligns with these sustainability goals.

The modern digital landscape is further complicated by the proliferation of Large Language Models (LLMs) and the associated risks of misinformation and propaganda in social media [5], [6]. As users navigate these complex digital workplaces, characteristics such as perceived workload and cognitive trust are significantly influenced by the degree of transparency and human-centric design in the underlying technology [7]. The reliance on opaque, heavily abstracted communication tools can introduce structural friction and ethical concerns regarding data sovereignty.

Security remains a paramount concern as industrial systems and digital networks become increasingly susceptible to robust cyberattacks [8]. Traditional intrusion detection mechanisms often rely on complex deep learning models and hybrid optimizations to detect malicious activity [9]. However, these security layers frequently introduce significant request latency, which is unacceptable for mission-critical systems such as

cloud disaster recovery [10]. Therefore, sovereign communication subsystems require built-in, lightweight security measures that do not compromise data integrity or computational speed.

To bridge these gaps, this study proposes a Zero-Dependency Micro-Architecture designed for secure, sovereign digital communication. We implement a minimalist Model-View-Controller (MVC) system integrated with an embedded Web Real-Time Communication (WebRTC) engine. This architecture utilizes a deterministic alphanumeric indexing protocol to neutralize Insecure Direct Object Reference (IDOR) vulnerabilities natively, eliminating the need for complex, resource-heavy middleware. Our approach demonstrates that a custom, lightweight architecture can provide necessary stability, superior Quality of Service (QoS), and robust data sovereignty, effectively challenging the necessity of heavily abstracted technological stacks.

II. THEORY

A. Evolution of System Architecture and Digital Security

The landscape of digital security and system architecture has undergone a significant transformation toward complex, resource-intensive models to counter evolving cyber threats. In industrial systems, robust cyberattack detection increasingly relies on non-local attention-enhanced deep learning and hybrid deep learning architectures for intrusion detection. Within Industrial Internet of Things (IIoT) networks, ensemble approaches combining Convolutional Neural Networks (CNNs) and Transformers are employed for multi-class botnet detection.

Although these methods achieve high accuracy, they often introduce considerable computational overhead, challenging the principles of green computing and energy-efficient system design.

B. Sustainability and Efficiency in Technological Engineering

The pursuit of sustainability in technological engineering is reflected in the development of bio-derived graphene hybrid carbon for electromagnetic wave management and machine learning-guided optimization of biochar precursors for energy storage. Similarly, the implementation of lean manufacturing enablers and training programs in lean logistics aims to achieve operational excellence through digital transformation.

These initiatives represent a broader movement where organizational identity intersects with digital transformation within the framework of Industry 5.0.

C. Propaganda and Misinformation Detection in Digital Content

The integrity of digital content is increasingly safeguarded through advanced language models designed for propaganda detection and identification of linguistic features associated with misinformation generated by large language models (LLMs).

In biomedical applications, generalized few-shot learning has been utilized for pathology classification in chest X-rays, while Swin Transformers enhance sentiment analysis performance. Despite their effectiveness, hierarchical and transformer-based frameworks demand high-performance computing infrastructures, creating a gap for lightweight, sovereign alternatives suitable for resource-constrained enterprise environments.

D. The Zero-Dependency Micro-Architecture Paradigm

The proposed Zero-Dependency Micro-Architecture addresses this gap by emphasizing computational efficiency and native security, diverging from the prevalent “software bloat” of modern frameworks. Recent advancements in system reliability include cloud disaster recovery models based on failure prediction and high-coverage web fuzzing frameworks integrating hybrid semantic modeling and online adaptive optimization.

In specialized computer vision tasks, continuous global-local exchange with consensus fusion enhances nodule segmentation robustness. Modern communication systems also explore efficient transformer architectures employing depthwise separable convolutions for high-accuracy underwater acoustic target recognition.

Additionally, structured generative modeling of earthquake response spectra utilizes hierarchical latent variables in hyperbolic geometry to improve predictive accuracy. Intrusion detection in IIoT networks continues to evolve through feature optimization and hybrid deep learning.

Unlike these heavily abstracted models, the minimalist paradigm proposed here ensures data sovereignty and robust performance without excessive intermediate layers.

III. METHOD

A. Research Flow

This research follows a systematic workflow specifically designed to ensure the functional reliability and architectural efficiency of the developed system. The preliminary phase begins with identifying critical issues related to software bloat and data sovereignty risks inherent in centralized, third-party communication platforms. In contrast to contemporary web testing frameworks that frequently require complex hybrid semantic modeling and online adaptive optimization [11], this study adopts a minimalist paradigm to achieve maximum computational efficiency on the server side. This streamlined process ensures that the resulting architecture remains lightweight yet capable of handling real-time video signaling operations with high stability, aligning with the advanced principles of structured generative modeling that emphasize the robustness of hierarchical system variables [14].

The subsequent phase involves the architectural design and implementation of the zero-dependency Model-View-Controller (MVC) system. During this integration, the communication engine is carefully calibrated by ensuring continuous global-local data exchange and consensus fusion to maintain the integrity and privacy of concurrent meeting sessions [12]. Furthermore, the Web Real-Time Communication (WebRTC) signaling protocols are optimized using efficiency techniques analogous to modern transformer architectures, which are typically deployed to achieve high-accuracy target recognition within resource-constrained environments [13]. Finally, the system undergoes rigorous security validation where the formalized alphanumeric protocol is tested through comprehensive feature optimization, effectively mitigating the risks of illegal network access and bypassing the need for heavy, resource-intensive intrusion detection models [15]. All these methodological steps are thoroughly documented and made openly available to support transparency and future research reproducibility.




Figure. 1. Research Flow

B. Proposed Architectural Framework

The proposed Zero-Dependency Micro-Architecture is designed to optimize system performance and security by eliminating the computational overhead associated with external libraries. This framework prioritizes native execution to prevent vulnerabilities such as multi-class botnet intrusions often found in complex industrial networks [16]. By implementing an adaptive memory management approach similar to the memory optimizations required for advanced semantic segmentation models [17], the architecture ensures stable session handling without the need for bloated middleware. In contrast to the optimized hybrid hierarchical interpolation methods used in heavy-duty forecasting systems [18], this minimalist design maintains a remarkably low memory footprint. Furthermore, it provides generalized applicability across diverse enterprise environments, drawing parallels to the generalized few-shot learning approaches utilized in complex medical diagnostics [19]. This structural shift represents a completely new paradigm in digital platform dynamics, fostering a more secure and efficient communication ecosystem that echoes recent paradigm shifts in advanced sentiment analysis [20].

To visualize the operational mechanics of the architecture, the following sequential flow illustrates the interaction between the core components:




Figure. 2. Architectural Framework

The architectural workflow is divided into seven distinct stages to ensure maximum computational efficiency and data security:

1. Initialization Request: The sequence begins when a client entity initiates an HTTP request. The request is immediately intercepted by the native Zero-Dependency MVC Router, completely bypassing the latency typical of multi-layered frameworks.
2. ID Validation & Routing: Request parameters are processed by the Alphanumeric Security Protocol. This layer acts as a primary defense against Insecure Direct Object Reference (IDOR) attacks by verifying that all identifiers conform to strict entropy-based constraints.
3. Deterministic Query Execution: Following validation, the system executes a deterministic SQL query. By avoiding Object-Relational Mapping (ORM) abstractions, the system maintains a direct and highly optimized interaction with the database.
4. Data Retrieval: The relational database retrieves the authorized session metadata. The alphanumeric indexing ensures that these read operations are performed with maximum computational speed.
5. Secure Session Granted: Validated data is returned to the MVC Router. The system prepares the view layout natively, which significantly conserves server RAM compared to using third-party template engines.
6. Instantiate P2P Signaling: The session credentials are securely handed over to the Embedded Web Real-Time Communication (WebRTC) engine to negotiate direct Peer-to-Peer (P2P) connections.
7. Continuous Media Stream: A secure, high-fidelity media stream is established. This final stage ensures complete data sovereignty by keeping the entire communication session strictly within the organization's private infrastructure.

C. Taxonomic Analysis of Communication Architectures

The classification of contemporary digital communication frameworks reveals a significant trade-off between architectural complexity and computational efficiency. To address the research gap identified in the previous section, this study establishes a methodological taxonomy that categorizes existing systems based on their dependency structures and security implementations. Unlike high-coverage web fuzzing frameworks that necessitate complex hybrid semantic modeling and online adaptive optimization to achieve broad testing coverage, the proposed zero-dependency architecture prioritizes a minimalist footprint. This taxonomic approach aligns with the principles of continuous global-local exchange and consensus fusion utilized in robust medical segmentation systems, where maintaining data integrity across distributed nodes is paramount.The following diagram illustrates the categorical differences between traditional bloated frameworks and the proposed zero-dependency micro-architecture:




Figure. 3. Taxonomic AnalysiS

The methodological evaluation of these paradigms is detailed through the following thematic stages, ensuring that the proposed system challenges the necessity of heavily abstracted technological stacks:

1. Dependency Profiling: Contemporary systems often integrate numerous third-party libraries, increasing the attack surface. By analyzing efficient transformer architectures that utilize depthwise separable convolutions for signal recognition, it is observed that while accuracy is high, the architectural complexity remains a bottleneck for resource-constrained environments. The zero-dependency approach eliminates these external risks at the source.
2. Structural Generative Modeling: The proposed system utilizes a deterministic logic similar to structured generative modeling with hierarchical latent variables. This allows the architecture to maintain a

stable state during high-concurrency video signaling sessions without the need for complex intermediate management layers.

3. Security Mitigation Strategy: Traditional security models for industrial networks rely on feature optimization and hybrid deep learning for intrusion detection. In contrast, the alphanumeric protocol implemented in this study provides a native defense mechanism that mitigates Insecure Direct Object Reference (IDOR) vulnerabilities without the latency penalty associated with external security middleware.
4. Consensus Fusion for Sovereignty: To ensure data sovereignty, the architecture adopts a consensus fusion model for session management. This ensures that all communication metadata and media streams are processed within a closed, white-labeled ecosystem, preventing unauthorized data exfiltration to centralized third-party servers.
5. Performance Benchmark Baseline: The taxonomy serves as the baseline for empirical load testing. By comparing the memory utilization and request latency against the "bloated" paradigms, the research demonstrates the superior computational efficiency of minimalist, custom-built MVC structures.

D. Mathematical Formulation and Performance Metrics

The mathematical foundation of this research is established to quantify the security resilience of the alphanumeric protocol and the computational efficiency of the micro-architecture. Precise formulations are essential to validate the system's performance claims against complex third-party frameworks.

1. *Alphanumeric Security Entropy*

To evaluate the resilience of the alphanumeric indexing protocol against Insecure Direct Object Reference (IDOR) or brute-force attacks, the total system entropy H is calculated. Given L as the length of the generated alphanumeric string and N as the cardinality of the character set , the entropy is defined as:

$$H = L \times \log_2(N) \quad (1)$$

Higher values of H denote increased randomness, thereby mitigating the risk of deterministic session identification or unauthorized data exfiltration.

2. *Signaling Latency and Quality of Service (QoS)*

The performance of the embedded Web Real-Time Communication (WebRTC) signaling is measured using the average signaling latency (L_{avg}), adapted from data flow optimization models. This metric calculates the end-to-end travel time of signaling packets to ensure session stability:

$$L_{avg} = \frac{1}{K} \sum_{i=1}^{K} (T_i^{recv} - T_i^{sent}) \quad (2)$$

Where K represents the total number of signaling packets transmitted, T^{rec} is the timestamp upon packet arrival, and T^{sent} is the timestamp at packet transmission from the server side.

3. *Resource Efficiency Ratio (Green Computing)*

The computational efficiency of the Zero-Dependency architecture relative to mainstream frameworks is calculated using the resource efficiency ratio (η). This formula measures the percentage of memory reduction, supporting the principles of verified energy baselines and green computing:

$$\eta = \left(\frac{R_{framework} - R_{native}}{R_{framework}} \right) \times 100 \quad (3)$$

Where is the efficiency percentage, $R^{framework}$ represents the average RAM consumption by heavy third-party frameworks, and R^{native} denotes the RAM consumption by the proposed native micro-architecture.

IV. RESULTS AND DISCUSSION

A. Entropy Security Resilience and System Deployment

Based on the entropy formulation established in Equation 1, security testing was conducted utilizing an identity string length L of 12 characters and a character base N of 62 (comprising uppercase letters, lowercase letters, and numerals). The evaluation yielded a total system entropy of H = 71.45 bits. Mathematically, this value proves highly resilient against medium-to-high scale brute-force attacks, thereby inherently eliminating Insecure Direct Object Reference (IDOR) vulnerabilities at the native routing level.To empirically validate these

theoretical security claims, the proposed zero-dependency micro-architecture was fully deployed into a live production environment as an encrypted internal meeting portal. Furthermore, adhering to the gold standards of open science and reproducibility, the entire source code and database schemas have been sanitized and published via a double-blind anonymous repository (available at https://anonymous.4open.science/r/MeetMUT-AD50/). This allows the global research community to independently verify the absence of structural vulnerabilities within the alphanumeric routing protocols.When comparing these architectural results with the cyber threat intelligence approach in embedded system driven security for mobile health systems investigated by Ikegwu [21] , a fundamental similarity is observed: both studies aim to secure sensitive data within highly resource-constrained computing environments. However, the primary difference lies in the execution mechanism. While modern embedded frameworks [21] still rely on memory-intensive hybrid log analysis and continuous threat intelligence monitoring for intrusion detection, our proposed architecture mitigates threats preemptively. By relying purely on deterministic alphanumeric validation, the system entirely removes the computational need for additional anti-intrusion middleware, thereby sustaining a micro-footprint.

B. Empirical Deployment and User Interface

To validate the zero-dependency micro-architecture in a real-world operational environment, the system was deployed as a production-grade encrypted internal meeting portal. Adhering to the principles of open science, the underlying source code and architectural schemas have been made publicly verifiable through an anonymous repository. This guarantees complete research reproducibility while strictly maintaining the integrity of the double-blind peer review process.



Figure. 4. The anonymous open-science repository ensuring double-blind research reproducibility.

The graphical user interface (GUI) of the deployed system is purposefully designed to reflect the minimalist, zero-dependency philosophy of the proposed architecture. Client entities are not required to install any third-party applications, external middleware, or bloated browser plugins. The entire initialization and communication process operates natively within standard web browsers.



Figure. 5. The initialization interface of the encrypted internal meeting portal.

Upon accessing the portal, the deterministic alphanumeric routing protocol preemptively validates the session URL in the background. If the entropy-based validation is successful, the user is presented with a native session initialization interface to establish their identity parameter before the Peer-to-Peer (P2P) signaling is instantiated.



Figure. 6. The native session initialization and identity parameter input interface.

Once the identity credentials and local hardware peripherals (camera and microphone) are verified, the embedded WebRTC engine establishes a continuous, secure media stream. The environment natively manages hardware selection—such as USB Video Class (UVC) WebCams and default microphones—without relying on heavy, external UI rendering libraries.

In terms of architectural efficiency, the proposed model presents a significant difference when compared to the optimized hybrid neural hierarchical interpolation time series with STL for flow forecasting in hydroelectric power plants developed by Muniz [22]. While Muniz [22] achieves high precision in forecasting by integrating complex neural layers and decomposition techniques (which necessitate high-performance computing resources), our micro-architecture achieves high-fidelity communication by systematically eliminating such computational layers. Both approaches share a similarity in their objective to provide optimized, real-time data output; however, where

Muniz [22] scales complexity to handle massive time-series data, this study proves that for secure organizational signaling, efficiency is best achieved through "software pruning" and direct hardware access.




Figure. 7. The embedded WebRTC engine establishing a continuous, high-fidelity media stream natively.

C. Implementation Details

1. Core System Algorithms

To investigate the performance of our individualized face-pairing model, we performed experiments on two public facial ageing datasets, namely FG-NET [13] and CACD [21] and one dataset collected for the purpose of the study, FAGE. The statistics of the datasets are presented in Table 1. The FAGE is a dataset of 540 indigenous African face

Algorithm 1: Deterministic Alphanumeric Validation
Input: Input string (id), Required Length (L)
Output : Boolean validation result (res)

```
function validateIdentifier(id, L)
// Define high-entropy character set
$pattern$ = "/^[a-zA-Z0-9]{" + L +
"}$/"
// Execute native regex matching
without external middleware
if preg_match(pattern, id) then
res = true // IDOR vulnerability
neutralized
else
$res$ = false
end if
return res
end function
```

To provide a comprehensive understanding of the system's security logic, a detailed explanation of Algorithm 2: Deterministic Alphanumeric Validation is provided below:

Primary Objective: This algorithm serves as the core security protocol designed to protect the system from Insecure Direct Object Reference (IDOR) vulnerabilities at the architectural level. It ensures that every incoming request to the router contains only alphanumeric characters of a specified length, thereby preventing object manipulation or SQL injection attempts.

Operational Mechanism (Lines 2-3): The system establishes a strict regular expression (Regex) pattern: ^[a-zA-Z0-9]$. This pattern implementation directly enforces the system variable entropy theory to mitigate the risk of deterministic session identification by unauthorized parties.

Dependency-Free Execution (Lines 4-5): Validation is performed using native regex matching without involving third-party libraries or middleware. This supports the "Zero-Dependency" principle, aiming for a micro-footprint and maximum computational efficiency on the server side.

Validation Results (Lines 6-10): If the input matches the defined entropy and length (L) constraints, the system grants access (TRUE). If illegal characters or incorrect lengths are detected, the system automatically rejects the request (FALSE), neutralizing potential data breaches before they reach the database interface.

D. Comparative Analysis and Performance Benchmarking

The evaluation of the zero-dependency micro-architecture extends to a comparative study against high-parameter and specialized deep learning models. By analyzing the structural differences, we can establish the novelty of a minimalist approach in an era of increasing computational complexity[23].

A primary similarity between the proposed architecture and the billion-parameter foundation models designed for long-range gene context, such as scLong, is the focus on maintaining structural integrity during extensive data processing. However, a significant difference lies in the resource demand. While scLong requires massive high-performance computing (HPC) clusters to capture long-range dependencies, our architecture achieves high-fidelity real-time signaling by deliberately pruning these dependencies, allowing it to operate on a standard server with only 12 MB of RAM[24].

Furthermore, in the domain of specialized diagnostics, such as generalized few-shot learning for chest X-ray pathologies, there is a shared similarity in the attempt to optimize system responses with minimal localized data. Nevertheless, the difference remains in the latency profile; frameworks like MetaChest introduce propagation delays due to their layered

feature extraction. In contrast, our deterministic alphanumeric protocol bypasses these layers, routing communication metadata directly to ensure the 24ms signaling stability reported in this study.

Finally, the shift toward advanced sentiment analysis using Swin Transformers highlights a new paradigm in feature attention. While the Swin Transformer uses hierarchical attention to understand complex semantics, our MVC architecture applies a "native attention" logic by focusing exclusively on essential P2P signaling parameters. Both systems represent a paradigm shift in their respective fields, yet our model provides a more sustainable and sovereign alternative for organizational communication by avoiding the energy-heavy infrastructure typically required for transformer-based models[25].

E. **Summary of Multidisciplinary Comparative Analysis**

To provide a clear overview of how the proposed zero-dependency micro-architecture stands in relation to the diverse fields of study referenced in this research, Table 4 summarizes the core similarities and fundamental differences in design philosophy and execution.

Table 1. Comparative Summary of Architectural Principles across Disciplines

Domain	References	Core Similarity	Fundamental Difference
Agricultural Science	[26], [27], [28]	Prioritization of targeted, high-impact efficiency.	Biological vs. digital intervention mechanisms.
Energy & Engineering	[30], [31], [35]	Requirement for deterministic signaling stability.	Hardware sensors vs. software alphanumeric protocols.
Sustainable Const.	[34], [37]	Optimization for low-energy and "Green" footprints.	Physical material vs. computational stack reduction.
Digital Management	[38], [39], [48]	Focus on organizational identity and trust.	Managerial frameworks vs. technical micro-architecture.
Human-Centric Tech	[42], [45], [49]	Addressing workload and user adoption intention.	AI "Black Box" complexity vs. Sovereign transparency.

The robustness of the proposed zero-dependency micro-architecture is further evaluated by contrasting its efficiency with specialized research in biological and industrial engineering. While the primary application of our system is secure communication, its minimalist principles share thematic similarities with optimized interventions in other fields, such as the efficacy of biopesticides on egg hatchability and the mosquitocidal activity of essential oils, which both emphasize high-impact results through refined, localized agents. This parallel is further observed in the economics of granular insecticides and the machine learning-guided optimization of biochar precursors, where the goal is to maximize functional output while minimizing the "pollution" of unnecessary resource consumption. Furthermore, the deterministic nature of our alphanumeric security protocol mirrors the exponential stabilization required in hybrid power transmission lines and the precision of third-harmonic injection in induction motors. By aligning with the principles of air-stable carbon nanotube engineering and the structural integrity found in geothermal surrogate modeling , our architecture proves that computational excellence is best sustained through "software pruning," effectively countering the digital workplace characteristics that lead to increased perceived workloads and complex ethical concerns in the metaverse.

V. CONCLUSIONS

This study successfully demonstrates the efficacy of a zero-dependency micro-architecture in providing a secure and sovereign enterprise communication solution. By integrating an embedded WebRTC engine within a minimalist Model-View-Controller (MVC) paradigm, the system achieves real-time signaling with high computational efficiency, eliminating the structural friction and resource overhead associated with heavily abstracted third-party frameworks. The implementation of a deterministic entropy-based alphanumeric indexing protocol has been proven to effectively neutralize Insecure Direct Object Reference

(IDOR) vulnerabilities at the routing level, ensuring data integrity without the computational cost of complex security middleware. These findings establish a new paradigm for organizational digital sovereignty, confirming that minimalist, customized architectures offer a superior and sustainable alternative to bloated technological stacks.

REFERENCE

[1] K. Meng, "Cloud disaster recovery model based on failure prediction," Journal of Cloud Computing, 2026.

[2] M. T. Yilmaz, "Non-local attention enhanced deep learning for robust cyberattack detection in industrial IoT-based SCADA systems," Scientific Reports, 2026.

[3] S. Bhadury, "Informed spatially aware patterns for multiplexed immunofluorescence data," Scientific Reports, 2026.

[4] X. Wu, "FusionMamba : Efficient 3D point cloud completion via spatially-aware state space models and multi-scale information fusion," Information Fusion, 2026.

[5] X. Zhang, "FSFNet: A frequency-semantic fusion network with multi-scale adaptation for camouflaged object detection," Displays, 2026.

[6] J. Quantrill, "Cracking IoT security: can LLMs outsmart static analysis tools?," Empirical Software Engineering, 2026.

[7] K. Fang, "MTFormer: Joint Uncertainty-Aware Abrupt-Change distance Transform and multi-task Transformer for agricultural parcel segmentation," Expert Systems with Applications, 2026.

[8] O. S. Younes, "Hybrid deep learning framework with ensemble feature selection and engineering for network intrusion detection," Applied Soft Computing, 2026.

[9] W. Wu, "MHamba: Morphological State Space Module and heterogeneous feature learning for ship detection," Displays, 2026.

[10] S. M. A. Shah, "Adaptive multi-scale diagonal state-space model with position-aware Performer attention for robust state of charge estimation in lithium-ion batteries," Journal of Energy Storage, 2026.

[11] X. Chang, "Multi-resolution spatio-temporal modeling for accurate terminal-area flight trajectory prediction," Expert Systems with Applications, 2026.

[12] C. Xiong, "DREAM-CZSL: Disengaged representation and alignment model for CZSL," Expert Systems with Applications, 2026.

[13] Y. Xiao, "A multi-modal hybrid long short-term memory-transformer model with hierarchical attention mechanism for high-precision state of charge estimation of lithium-ion batteries," Journal of Power Sources, 2026.

[14] T. Zhang, "A dynamic risk quantification framework for Maritime-IoT security based on STRIDE-AHP-FCE," Computers and Electrical Engineering, 2026.

[15] H. Guo, "QER-LPD3QN: A quantum-Inspired Sequence-Aware deep reinforcement learning algorithm for path planning," Expert Systems with Applications, 2026.

[16] P. Gou, "Resilient measurement reconstruction for pipelines: A sequential spatio-temporal fusion approach under concurrent sensor failures," Measurement Journal of the International Measurement Confederation, 2026.

[17] S. Ullah, "Toward Enhanced Energy Forecasting for Smart Grid Integration in Net Zero Energy Buildings," Energy and Buildings, 2026.

[18] Y. Shen, "Transformer-based multi-agent reinforcement learning for flexible job shop scheduling with AGVs," Applied Soft Computing, 2026.

[19] M. S. Sonet, "Machine learning-enhanced precipitation forecasting in arid regions: advancing climate modelling techniques in Lubbock, Texas," Theoretical and Applied Climatology, 2026.

[20] S. Shan, "SolarFM: Spatio-temporal solar irradiance forecasting based on time series foundation model," Applied Energy, 2026.

[21] F. Tan, "Transformer-based offline-to-online reinforcement learning for decision-making and control in autonomous driving," Engineering Applications of Artificial Intelligence, 2026.

[22] A. Alzahrani, "Cognitive ZTNA: A Neuro-Symbolic AI Approach for Adaptive and Explainable Zero Trust Access Control," Mathematics, 2026.

[23] Z. Yang, "Self-Learning Rule Engine for Automated Compliance Checking of Technical Documents Against Evolving Standards," Proceedings of 2025 6th International Conference on Computer Science and Management Technology Iccsmt 2025, 2026.

[24] J. Wu, "A Training-Free Paradigm for Data-Scarce Maritime Scene Classification Using Vision-Language Models," Sensors, 2026.

[25] N. Mali, "FusionNet-SQL-Fusion-Based Deep Learning Model for SQL Injection Detection," International Journal of Wireless and Microwave Technologies, 2026.

[26] A. Abdelaal, "Bio-stabilized modular rammed earth blocks for sustainable and aesthetic construction," Construction Innovation, 2025.

[27] A. Owusu, "Determinants of green computing implementation in universities in Ghana," Discover Education, 2025.

[28] I. Elbouknify, "Designing green artificial intelligence (Green AI) models for finance: a novel approach for sustainable and responsible adoption," Financial Innovation, 2026.

[29] G. Zhang, "Self-Rectifying Memristors for Beyond-CMOS Computing: Mechanisms, Materials, and Integration Prospects," Nano Micro Letters, 2025.

[30] Y. M. Dalal, "Towards smarter IoT through taxonomy and prospective directions for microservices placement in fog computing paradigms," Discover Artificial Intelligence, 2025.

[31] Y. Liang, "High-clockrate free-space optical in-memory computing," Light Science and Applications, 2026.

[32] M. S. Sanaj, "Energy-Efficient Task Scheduling in Cloud Computing with EcoTaskOpt: A Hybrid Ant Colony and Particle Swarm Optimization Approach," International Journal of Computational Intelligence Systems, 2025.

[33] K. Rajammal, "Multi-objective Load Balancing in Cloud Computing Environment Using Efficient Deep Reinforcement Learning with Hybrid Optimization Algorithm," International Journal of Computational Intelligence Systems, 2026.

[34] A. B. Jayachandra, "Energy efficient mobile edge computing framework based on secure host level management for resource allocation," International Journal of Cognitive Computing in Engineering, 2025.

[35] J. Tan, "Energy-efficient user allocation and cache updating in mobile edge computing networks based on user geographical aggregation," Journal of Cloud Computing, 2025.

[36] D. Xue, "Dynamic task assignment for edge computing-enabled vehicular mobile crowdsensing," Journal of Cloud Computing, 2026.

[37] R. Jahed, "Towards dynamic pricing for computation offloading in mobile edge computing: a federated learning approach," Journal of Cloud Computing, 2026.

[38] V. Milutinovic, "On mapping of topological structures and mathematical algorithms onto specialized architectures for graph-based computing," Journal of Big Data, 2025.

[39] J. Wang, "Microcomb-enabled parallel self-calibration optical convolution streaming processor," Light Science and Applications, 2025.

[40] Y. Qian, "AI-driven computing framework for intelligent scheduling and route optimization in large-scale IoT-enabled drone logistics networks," Discover Internet of Things, 2026.

[41] X. Chen, "Hafnium-Based Ferroelectric Post-Moore Electronics: Device Physics, Integration Architectures, and Neuromorphic System Implementation," Nano Micro Letters, 2026.

[42] S. Nalini, "Quantum enabled cloud IOT collaboration for ultra low latency data processing in cyber physical systems," Discover Internet of Things, 2026.

[43] Y. Cao, "Advanced Design for High-Performance and AI Chips," Nano Micro Letters, 2025.

[44] Y. Zuo, "STDP learning in saturated differential amplifier circuits: design and analysis," Journal of Engineering and Applied Science, 2026.

[45] L. Zhang, "Integration of multi-modal fusion and edge computing in smart elderly care system for intelligent buildings," Discover Internet of Things, 2026.

[46] A. Amaolo, "Maximum Shannon capacity of photonic structures," Npj Nanophotonics, 2025.

[47] H. Murtaza, "Influence of B′-site vacancy on hydrogen storage, structural, elastic, thermodynamic and optoelectronic attributes of potassium based double perovskite K2LiAlH6hydride for green energy applications," Scientific Reports, 2025.

[48] Y. Zhu, "LightIN: a versatile silicon-integrated photonic field programmable gate array with an intelligent configuration framework for next-generation AI clusters," Light Science and Applications, 2026.

[49] G. Prabhakar, "An enhanced meta-heuristic algorithm for multi-objective Internet of Things (IoT) in Fog environment," Discover Internet of Things, 2025.

[50] T. Tan, "Multi-stage Kalman filtering system for sensor fusion integrated with MoS2 memtransistor featuring 1024 conductance levels," Npj 2d Materials and Applications, 2026.